

TECHNICAL SHEET

TYPICAL APPLICATIONS

- ☞ Kraft paper carton sealing tape suitable for manual and automated application.



ADVANTAGES AND BENEFITS

- ☞ Excellent adhesion even in recycled cartons.
- ☞ Good tack.
- ☞ Printable.
- ☞ Hand tearable.

CONSTRUCTION

- ☞ Backing: Kraft paper
- ☞ Adhesive: Synthetic rubber and hydrocarbon resins.
- ☞ Colour: Brown.



TECHNICAL DATA

	METRIC
Paper Thickness	90 Micron
Total Thickness	110 Micron
Peel Adhesion	8,5 N/cm
Tensile Strength	45 N/cm
Holding Power to Kraft @ 50°C in oven	100 hours
Application Temperature	6°C to 45°C
Service Temperature	-10°C to 60°C



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

STORAGE

Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.